

NEOX Products Quick Reference Guide

neoxnetworks.com	IDS, NDR, NSM, Log/PCAP			Full All Packet Capture, Forensics, and Analysis								Encryption/Decryption			Policy Control			Data Diode
	PacketOwl Series			PacketFalcon Series				PacketGrizzly Series			PacketShark Series			PacketDragon Series			PacketRoo Series	
																		
Key Features & Capabilities	Suricata-based IDS			On-Demand Capture (FPGA)				Extensible Capture (FPGA)			SSL & TLS Visibility			White List Control			Air Gap	
	On-Prem	VM	Cloud	Mini	Mini X	Compact	Portable	Lite	Heavy	ESU	1M	1L	1XL	S	M	L	Portable	
Throughput (Max)	100Gbps	Scalable	Scalable	10Gbps	25Gbps	100Gbps	100Gbps	100Gbps	100Gbps	N/A	15Gbps	25Gbps	50Gbps	100Mbps	1Gbps	10Gbps	1Gbps	
Throughput (Max) - Threat Analysis or SSL/TLS	100Gbps	Scalable	Scalable	N/A	N/A	N/A	N/A	N/A	N/A	N/A	7Gbps	13Gbps	25Gbps	100Mbps	1Gbps	10Gbps	10Gbps	
Threat IP(s) Filtering	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	10M	10M	10M	N/A	
Event Handling (Per-Min)	1M	Scalable	Scalable	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
Event Logging (Per-Min)	2G	Scalable	Scalable	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
Capture-to-Disk Rate	25Gbps	Scalable	Scalable	10Gbps	25Gbps	100Gbps	100Gbps	100Gbps	100Gbps	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
Sustained Capture-to-Disk (No Packet Loss)	✓	✓	✓	✓	✓	✓	✓	✓	✓	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
400G QSFP-DD Ports (100G Break Out) (Max)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
100G SFP28 Ports (40G Break Out) (Max)	2 (2)	Scalable	Scalable	N/A	N/A	4 (4)	6 (6)	8 (8)	8 (8)	N/A	8 (8)	8 (8)	8 (8)	N/A	N/A	N/A	N/A	
25G SFP28 or 10G SFP+ Ports (Max)	4 (4)	Scalable	Scalable	4	4	8 (16)	12 (24)	16 (32)	16 (32)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
10G SFP+ or 1G SFP Ports (Max)	4 (8)	Scalable	Scalable	4	4	8 (16)	12 (24)	16 (32)	16 (32)	N/A	32	32	32	4	4	4	N/A	
10/100/1000 RJ45 Ports (Max)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	64	64	64	8	8	8	2	
Virtual Ports (Max)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
Onboard Storage (Min - Max)	90 - 720TB	90 - 720TB	90 - 720TB	8 - 32TB	8 - 32TB	30 - 300TB	24 - 480TB	38 - 307TB	38 - 720TB	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
Onboard + External Storage (Min - Max)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	2 - 9PB	2 - 8PB	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
SSD Storage	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	N/A	N/A	N/A	N/A	N/A	N/A	
Encrypting Storage (SED)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
Transparent (No MAC/IP Address)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	✓	
Encrypted Firmware	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
SSL/TLS 1.3 Support	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	✓	✓	✓	N/A	N/A	N/A	N/A	
URL Classification & URL Filtering	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	✓	✓	✓	N/A	N/A	N/A	N/A	
Policy-based Traffic Control	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	✓	✓	✓	N/A	N/A	N/A	N/A	
Jumbo Frames (10K) Support	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	N/A	N/A	N/A	✓	
Multiple Capture Merge	N/A	N/A	N/A	X	X	X	X	X	X	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
Out-of-the-Box Dashboards	N/A	N/A	N/A	✓	✓	✓	✓	✓	✓	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
Application Identification	N/A	N/A	N/A	✓	✓	✓	✓	✓	✓	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
TCP Analysis	N/A	N/A	N/A	✓	✓	✓	✓	✓	✓	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
Latency/Jitter Analysis	N/A	N/A	N/A	✓	✓	✓	✓	✓	✓	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
Multicast Video Analysis	N/A	N/A	N/A	✓	✓	✓	✓	✓	✓	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
Data Correlation and Baselining	N/A	N/A	N/A	✓	✓	✓	✓	✓	✓	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
Data Diode Intrusion Prevention (Air Gap)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	✓	
IEC 62443 Security Compliance	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	X	
CRITIS Compliance	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	✓	
FIPS 140-2 Compliance	N/A	N/A	N/A	X	X	✓	✓	✓	✓	N/A	X	X	X	X	X	X	X	
TAA Compliance	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Software Subscription (Year)	N/A	N/A	N/A	1 / 3 / 5	1 / 3 / 5	1 / 3 / 5	1 / 3 / 5	1 / 3 / 5	1 / 3 / 5	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
Service and Support (Levels)	Silver/Gold	Silver/Gold	Silver/Gold	Silver/Gold	Silver/Gold	Silver/Gold	Silver/Gold	Silver/Gold	Silver/Gold	Silver/Gold	Silver/Gold	Silver/Gold	Silver/Gold	Silver/Gold	Silver/Gold	Silver/Gold	Silver/Gold	
Inline or Out-of-Band Deployment	OOB	OOB	OOB	OOB	OOB	OOB	OOB	OOB	OOB	OOB	Either	Either	Either	Either	Either	Either	OOB	
Rack Space (RU)	2RU	N/A	N/A	2RU	2RU	1RU	N/A	2RU	2RU	5RU	2RU	2RU	2RU	1RU	1RU	1RU	1RU	
Cards/Module Slots (Max)	N/A	N/A	N/A	N/A	N/A	2	2	1	1	N/A	8	8	8	N/A	N/A	N/A	N/A	
Airflow Direction	F > B	N/A	N/A	F > B	F > B	F > B	N/A	F > B	F > B	F > B	F > B	F > B	F > B	F > B	F > B	F > B	N/A	
Passive/No Power (Fiber only)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	X	
PoE 802.3af Passthrough	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
Power Options	1+1 AC	N/A	N/A	1+0 AC	1+0 AC	1+1 AC	1+0 AC	1+1 AC	1+1 AC	1+1 AC	1+1 AC	1+1 AC	1+1 AC	1+1 AC	1+1 AC	1+1 AC	1+1 AC	

✓: Supported, X: Not supported, N/A: Not applicable or not irrelevant, (): Using break-out cables

NEOX Products Quick Reference Guide

neoxnetworks.com  NEXT GENERATION NETWORK VISIBILITY Key Features & Capabilities		Network Packet Broker (NPB)																	Mgmt	
		PacketWolf Series			PacketLion Series								PacketTiger Series					Packet Director		
																				
		Low-Latency Services (FPGA)			High-Density Aggregation (ASIC)								Feature-Rich (CPU-based)					Virtual Broker	NPB Manager	
	100	200	400	3XL	4L	2L	2M	1L	1M	1S2	1SC	1XL	2XL/2XXL	1SCR	1M	1SC	Cloud			
Performance	Forwarding Throughput (Max)	100Gbps	200Gbps	400Gbps	12.8Tbps	8Tbps	3.2Tbps	3.2Tbps	2Tbps	2.1Tbps	2.1Tbps	108Gbps	800Gbps	200/400Gbps	45Gbps	24Gbps	23Gbps	Scalable	Scalable	
	Non-Blocking Architecture	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	N/A	N/A	
Density	Line-Rate Performance (No Packet Loss)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	N/A	N/A	N/A	N/A	N/A	
	Hardware Acceleration (DPDK)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	✓	✓	✓	✓	✓	N/A	N/A	
	400G QSFP-DD Ports (100G/40G Break Out) (Max)	N/A	N/A	N/A	32 (128/64)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
	100G QSFP28 Ports (40G Downspeed) (Max)	N/A	2 (2)	4 (4)	N/A	40 (40)	32 (32)	32 (32)	8 (8)	6 (6)	6 (6)	N/A	8 (8)	2 (2) / 4 (4)	N/A	N/A	N/A	N/A	N/A	
	40G QSFP+ Ports (10G Break Out) (Max)	N/A	2 (8)	4 (16)	N/A	40 (160)	32 (128)	32 (128)	8 (32)	6 (24)	6 (24)	N/A	8 (32)	2 / 4	N/A	N/A	N/A	N/A	N/A	
	25G SFP28 or 10G SFP+ Ports (Max)	4	(4)	(8)	N/A	N/A	N/A	N/A	48 (48)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
	10G SFP+ or 1G SFP Ports (Max)	4	(4)	(8)	N/A	N/A	N/A	N/A	N/A	48 (48)	48 (48)	6 (6)	32	8 / 16	4	2	2	N/A	N/A	
	10/100/1000 RJ45 Ports (Max)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	32	N/A	5	4	3	N/A	N/A	
	Virtual Ports (Max)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
	Stacking Ports (Dedicated)	N/A	N/A	N/A	N/A	13	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Key Features	Stacking	N/A	N/A	N/A	X	✓	✓	X	✓	X	✓	✓	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
	Port Labeling	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	N/A	
	Port Splitting	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	N/A	N/A	
	Port Mapping (1:1, N:N, N:1, 1:N)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	N/A	
	Load-Balancing (5 Tuple)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	N/A	
	Load-Balancing (GTP)	✓	✓	✓	X	✓ on TEID	✓ on TEID	✓ on TEID	✓ on TEID	X	✓ on TEID	✓ on TEID	✓	✓	✓	✓	✓	✓	N/A	
	Jumbo Frames Support	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	N/A	
	Filtering Rules	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	N/A	
	Filtering within Tunnel	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	N/A	
	User-Defined Filters	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	N/A	
	Header Stripping/Processing	✓	✓	✓	[✓]	[✓]	[✓]	[✓]	[✓]	[✓]	[✓]	[✓]	✓	✓	✓	✓	✓	✓	N/A	
	VLAN Stripping	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	N/A	
	MPLS Tag Stripping	✓	✓	✓	X	✓	✓	X	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	N/A	
	Packet Slicing/Truncation	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	N/A	
	Timestamping (NanoSec) with PTP/NTP	✓	✓	✓	N/A	N/A	N/A	✓ via NTP	✓ via NTP	N/A	✓ via NTP	X	✓	✓	✓	✓	✓	✓ via NTP	N/A	
	Timestamping with External PPS	✓	✓	✓	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	✓	✓	✓	✓	✓	✓	N/A	
	PTP/NTP Time Sync Management	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	N/A	
	Data Masking	✓	✓	✓	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	✓	✓	✓	✓	✓	✓	N/A	
	Flow Data (NetFlow/IPFIX) Export	✓	✓	✓	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	✓	✓	✓	✓	✓	✓	N/A	
	Packet Deduplication	✓	✓	✓	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	✓	✓	✓	✓	✓	✓	N/A	
	Metadata Export (Kafka)	✓	✓	✓	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	✓	✓	✓	✓	✓	✓	N/A	
	LDAP, RADIUS, TACACS+, CLI, Syslog, SNMP	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
	Traffic Aggregation/Replication	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	N/A	
	VXLAN/VNTAg Stripping	✓	✓	✓	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	✓	✓	✓	✓	✓	✓	N/A	
	GRE Tunnel Encapsulation/Decapsulation	✓	✓	✓	X	X	✓ L2 GRE	✓ L3 GRE	✓ L2 GRE	X	✓ L2 GRE	✓ L2 GRE	✓	✓	✓	✓	✓	✓	N/A	
	VLAN Tag Inner VLAN Filtering	✓	✓	✓	X	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	N/A	
	MAC-in-MAC DC Decapsulation	✓	✓	✓	X	X	X	X	X	X	X	X	✓	✓	✓	✓	✓	✓	N/A	
	GTP Correlation	X	X	X	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	✓	✓	✓	✓	✓	✓	N/A	
Local Packet Capture	✓	✓	✓	X	X	✓	X	✓	X	✓	✓	✓	✓	✓	✓	✓	✓	N/A		
Cert	GUI, Serial Console, and CLI	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	N/A	
	Optical Transceiver Diagnostics	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	N/A	N/A	
	PacketDirector Central Management	X	X	X	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	N/A	
	FIPS 140-2 Compliance	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	N/A	N/A	
Deployment	TAA Compliance	✓	✓	✓	X	X	X	X	X	X	X	X	X	X	X	X	X	N/A	N/A	
	Software Subscription (Year)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
	Service and Support (Levels)	Silver/Gold	Silver/Gold	Silver/Gold	Silver/Gold	Silver/Gold	Silver/Gold	Silver/Gold	Silver/Gold	Silver/Gold	Silver/Gold	Silver/Gold	Silver/Gold	Silver/Gold	Silver/Gold	Silver/Gold	Silver/Gold	Silver/Gold	Silver/Gold	
	Inline Mode (no bypass)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓ (+Bypass)	✓	✓	✓	✓	N/A	N/A	
	Rack Space (RU)	1RU	1RU	1RU	1RU	2RU	1RU	1RU	1RU	1RU	1RU	1RU	2RU	2RU	1RU	1RU	1RU	N/A	N/A	
Cards/Module Slots (Max)	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	4	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
Airflow Direction	F > B	F > B	F > B	F>B / B>F	F > B	F>B / B>F	F>B / B>F	F>B / B>F	F>B / B>F	F>B / B>F	F>B / B>F	F > B	F > B	F > B	F > B	F > B	N/A	N/A	N/A	
Power Options	1+1 AC/DC	1+1 AC/DC	1+1 AC/DC	1+1 AC/DC	1+1 AC/DC	1+1 AC/DC	1+1 AC/DC	1+1 AC/DC	1+1 AC/DC	1+1 AC/DC	1+1 AC/DC	1+1 AC/DC	1+1 AC/DC	1+1 AC/DC	1+1 AC/DC	1+1 AC/DC	N/A	N/A	N/A	
✓: Supported, X: Not supported, N/A: Not applicable or not irrelevant, (:): Using break-out cables, [:]: Limited functionality																				

NEOX Products Quick Reference Guide

NEOX Products Quick Reference Guide																		
		Network Test Access Point (TAP)								Future Products								
neoxnetworks.com		PacketRaven Series								PacketHawk Series								
NEOX NETWORKS NEXT GENERATION NETWORK VISIBILITY																		
Key Features & Capabilities		Remote Tap			Virtual Tap		Modular Tap		Inline-Bypass Switch/Tap									
		Standard	Hardened	Secure	VM	Cloud	Standard	Secure	Inline									
Perf	Throughput (Max)	400Gbps	1Gbps	400Gbps	Scalable	Scalable	400Gbps	400Gbps	100Gbps	2								
	TAP(s) per Rack Unit (RU)	3	3	3	N/A	N/A	30	30	2									
	400G QSFP-DD Ports (100G Break Out) (Max)	4 (16)	N/A	4 (16)	N/A	N/A	120 (480)	120 (480)	N/A									
Density	100G QSFP28 Ports (40G Break Out) (Max)	4 (4)	N/A	4 (4)	N/A	N/A	120 (120)	120 (120)	2 (2) + 2 (2) 1x Bypass Port Pair + 1x Bypass Port Pair									
	40G QSFP+ Ports (10G Break Out) (Max)	4	N/A	4	N/A	N/A	120	120	2 (2) + 2 (2) 1x Bypass Port Pair + 1x Bypass Port Pair									
	25G SFP28 or 10G SFP+ Ports (Max)	4	N/A	4	N/A	N/A	120	120	X									
	10G SFP+ or 1G SFP Ports (Max)	4	N/A	4	N/A	N/A	120	120	2 (2) + 2 (2) 1x Bypass Port Pair + 1x Bypass Port Pair									
	10/100/1000 RJ45 Ports (Max)	4	4	4	N/A	N/A	120	120	X									
Features	Virtual Ports (Max)	N/A	N/A	N/A	Scalable	Scalable	N/A	N/A	N/A									
	Transparent (No MAC/IP Address)	✓	✓	✓	✓	✓	✓	✓	✓									
	Secure Boot	X	✓	X	X	X	X	X	X									
	Encrypted Firmware	X	✓	X	X	X	X	X	X									
	Security Seals & Special Screws	X	✓	✓	N/A	N/A	X	X	X									
	Data Diode Intrusion Prevention	✓	✓	✓	X	X	X	✓	N/A									
	BiDi Functionality	✓	X	X	N/A	N/A	✓	✓	N/A									
	Jumbo Frames (16K) Support	✓	✓	✓	✓	✓	✓	✓	✓									
	IEC 62443 Security Compliance	X	✓	X	X	X	X	X	X									
	CRITIS Compliance	X	X	✓	X	X	X	✓	X									
Certs	FIPS 140-2 Compliance	X	X	X	X	X	X	X	X									
	TAA Compliance (Made in Germany)	✓	✓	✓	✓	✓	✓	✓	✓									
	Copper/Fiber	Both	Both	Fiber	N/A	N/A	Fiber	Fiber	Fiber									
Deployment	Inline or Out-of-Band Deployment	OOB	OOB	OOB	Inline	Inline	OOB	OOB	Inline									
	Split Ratio 50/50, 60/40, 70/30	✓	✓	✓	N/A	N/A	✓	✓	N/A									
	Breakout, Aggregation, Regeneration Mode(s)	✓	✓	✓	✓	✓	✓	✓	✓									
	Rack Space (RU)	1RU	1RU	1RU	N/A	N/A	1RU	1RU	1RU									
	Cards/Module Slots (Max)	N/A	N/A	N/A	N/A	N/A	30	30	2									
	Airflow Direction	N/A	N/A	N/A	N/A	N/A	N/A	N/A	F > B									
	Passive/No Power (Fiber only)	✓	X	✓	N/A	N/A	✓	✓	X									
	PoE 802.3af Passthrough	✓	✓	N/A	N/A	N/A	N/A	N/A	N/A									
	Power Options	1+1 AC/DC	1+1 AC/DC	N/A	N/A	N/A	N/A	N/A	1+1 AC									

✓: Supported, X: Not supported, N/A: Not applicable or not irrelevant, (): Using break-out cables